



Art	E-nr	Färg	RAL
1240AL	7747385	ALUMINIUM	9006
1240GR	7747386	GRAFIT	7016

Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Klart polykarbonat, UV stabiliserat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Ej dimbar
Nettovikt armaturen	11,03kg
Förpackning mått [cm]	22,5x22,5x103,5
LED	CREE XP-G2 7A3Q4 3000K
Drivdon	Meanwell LPHC-18-700 700mA 6-25V
Led modul effekt	14,7W
Armatur effekt	17,5W
Lumen modul	1380lm
Lumen ut	559lm
Led modul effekt	93,9lm/W
Armaturens effekt	31,9lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	50 000h
Energieffektivitetsindex (EEI)	A+
Effektfaktor	PF 0,49
Ta nominel:	+25°C
Inrush current	50A/190µs
Antal armaturer p/automatsäkring	B 10A: 8, B 16A: 14

