



Art.nr	El.nummer	Farge	RAL
891GA	3110090	GALVANISERT STÅL	-
891B	3110092	SORT	9005

## Generell informasjon

Type armatur	
Materiale	Galvanisert stål Galvanisert stål og lakker stål
Avdeknings materiale/optikk	Klar polykarbonat, UV stabilisert
Type lyskilde	LED modul + driver
Lysstyring	Ikke dimbar
Netto / Brutto vekt armatur	8,6kg / 9,1kg
Forpakkingsstørrelse [cm]	15x15x91
4xLED moduler	Cree JK3030 3000K no.1805004
Driver	OSRAM OT FIT 15/220-240/500 LT2 S
Effekt W	9,9W
Armatureffekt	12,7W
Modul lumen	1424lm
Lumen ut	593lm
Modul effektivitet	143,8lm/W
Armatur Lumen/Watt	46,7lm/W
ULOR	0%
Fargetemperatur	3000K
Farvekonsistens (McAdam-Ellipse)	SDCM3
Fargegjengivelsesindeks	80
Beregnet levetid L70/B50 ved 25°C	50 000h
Energieffektivitetsindeks (EEI)	<b>A++</b>
Virkningsgrad	PF > 0,85
Ta nominel:	+25°C
Inrush current	24A/174µs
Antall armaturer på automatsikring	<b>B 10A: 17, B 16A: 28, C 10A: 29, C 16A: 47</b>

## Filer som kan lastes ned

Manual