



Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	Classic design ceiling luminaire. For lighting private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ømm, spacing mm.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x1,5mm ² . A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED Gu10 lamp, 25D Replaceable light source by an end-user.
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,53kg / 1,63kg

Technical data

2 LED GU10 lamps.	Philips MASTER LED ExpertColor 3.9-35W GU10 927 25D (Datasheet)
Light source wattage	2 x 3,9W
Luminaire wattage	7,8W
Lamp luminous flux	530lm
Luminaire luminous flux	420lm
Light source efficiency	67,9lm/W
Efficiency of the luminaire	53,8lm/W
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	90
Rated life time L70/B50 at 25°C	40 000h
Power Factor luminaire	PF >0,8
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A G**

Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10 Philips Master LED max 4W PAR16 Gu10

Spare parts

46102507 LED Gu10 lamp.

Files to download

Photometric LDT files Photometric IES files
Manual

Indexes

Index	Color	RAL
1731AL	ALUMINIUM	9006
1731B	BLACK	9005
1731GR	GRAPHITE	7016
1731W	WHITE	9003