

## Type of luminaire


Type of luminaire	Wall luminaire.
Characteristics of the luminaire	Classic design ceiling luminaire. For lighting private areas and public spaces.

## General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: 2 holes $\varnothing$ 4.5mm, spacing 37mm x 97.5mm
Terminal	Connection terminals: max 3x2.5mm <sup>2</sup> , Possibility of connecting the luminaire in loops max 3x1.5mm <sup>2</sup> , Round insulated cable with a diameter of $\varnothing$ 7 ... 10.5mm
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,45kg / 1,58kg
Box dimensions [cm]	23x12,5x9

## Technical data

2 LED modules	Lumens EDC 38C 8W xxx 230V A Ver.1.2 (Datasheet)
External control	Dimmers Lumens LED AC (User manual)
Light source wattage	2x8W
Luminaire wattage	16W
Lamp luminous flux	1512lm
Luminaire luminous flux	1126lm
Efficiency of the luminaire	70,4lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,98
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+35°C

This product contains light sources of energy efficiency class **A** 

Inrush current	70mA / 60ms
----------------	-------------

## Spare parts

4699102301	LED module.
ZS1732zx0009	Service set.

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
1732AL	ALUMINIUM	9006
1732B	BLACK	9005
1732GR	GRAPHITE	7016
1732W	WHITE	9003