



| Art | E-nr | Färg | RAL |
|--------|---------|-----------|------|
| 1247AL | 7747379 | ALUMINIUM | 9006 |
| 1247GR | 7747380 | GRAFIT | 7016 |

Allmän information

| | |
|-----------------------------------|-------------------------------------------------------|
| Typ armatur | |
| Material | Pulverlackerad aluminium |
| Diffuser/Avskärmning: | Klart polykarbonat, UV stabiliserat |
| Typ ljuskälla | LED modul + driver |
| Ljusstyrning | Bakkantsdimmer |
| Nettovikt armaturen | 4,84kg |
| Förpackning mått [cm] | 22,5x22,5x37 |
| LED | 1305003G2 CREE XD16 3000K |
| Drivdon | Philips Xitanium 7W 0.35A 20V TE SC |
| Led modul effekt | 6,6W |
| Armatur effekt | 8,4W |
| Lumen modul | 798lm |
| Lumen ut | 308lm |
| Led modul effekt | 120,9lm/W |
| Armaturens effekt | 36,7lm/W |
| ULOR | 2,6% |
| Färgtemperatur | 3000K |
| Färgbeständighet (McAdam ellipse) | SDCM3 |
| Färgtolkningsindex (CRI/Ra) | 80 |
| Nominell livstid L70/B50 vid 25°C | 50 000h |
| LED-fotobiologiskt hot | RG0 or RG1 |
| Energieffektivitetsindex (EEI) | A+ |
| Effektfaktor | PF 0,98 |
| Ta nominel: | +25°C |
| Inrush current | 1A/15,2µs |
| Antal armaturer på automatsäkring | B 10A: 157, B 16A: 250, C 10A: 260, C 16A: 425 |