



## Type of luminaire

Type of luminaire	Wall luminaire.
Characteristics of the luminaire	Classic design ceiling luminaire. For lighting private areas and public spaces

## General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing$ 4,5 mm, spacing 37 mm x 80 mm
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . Round insulated cable with a diameter of $\varnothing$ 7...10,5mm
Type of light source	Gu10 lamp
Light control	Phase-dimming (TRIAC).

## Technical data

LED GU10 lamp	Philips MASTER LED ExpertColor 3.9-35W GU10 927 25D (Datasheet)
Light source wattage	3,9W
Luminaire wattage	3,9W
Lamp luminous flux	265lm
Luminaire luminous flux	210lm
Light source efficiency	67,9lm/W
Efficiency of the luminaire	53,8lm/W
ULOR	0%
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	90
Rated life time L70/B50 at 25°C	40 000h
Power Factor luminaire	PF > 0,8
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

## Spare parts

ZS1741zx0009	Service set.
--------------	--------------

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
1741AL	ALUMINIUM	9006
1741B	BLACK	9005
1741GR	GRAPHITE	7016
1741W	WHITE	9003