



Type of luminaire	
Type of luminaire	Wall luminaire.
Characteristics of the luminaire	Classic design wall luminaire. For lighting private areas and public spaces

General information	
Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing$ 4,5 mm, spacing 37 mm x 80 mm
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . Round insulated cable with a diameter of $\varnothing$ 7...10,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,1kg / 1,16kg

Technical data	
LED module	Lumens EDC 38C 8W xxx 230V A Ver.1.2 (Datasheet)
Light source wattage	8W
Luminaire wattage	8W
Lamp luminous flux	756lm
Luminaire luminous flux	563lm
Light source efficiency	94,5lm/W
Efficiency of the luminaire	70,4lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,98
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+25°C

This product contains light source of energy efficiency class **A++**

Inrush current	35mA / 60ms
----------------	-------------

Spare parts	
ZS1742zx0009	Service set.

Files to download	
Photometric LDT files	Photometric IES files
Manual	

Indexes		
Index	Color	RAL
1742AL	ALUMINIUM	9006
1742B	BLACK	9005
1742GR	GRAPHITE	7016
1742W	WHITE	9003