



Art	E-nr	Färg	RAL
5123AL	7749140	ALUMINIUM	9006
5123GR	7749143	GRAFIT	7016

## Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Polykarbonat med optisk struktur, UV stabiliserat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Bakkantsdimmer
Netto / Bruttovikt armatur	6kg / 7kg
Förpackning mått [cm]	15x15x91
LED	Philips SLM C 840 1203 L09 1619 G7
Drivdon	Philips Xitanium 10W 0.25A 40V TE SC 230V
Led modul effekt	8,5W
Armatur effekt	9,3W
Lumen modul	1371lm
Lumen ut	322lm
Led modul effekt	161,3lm/W
Armaturens effekt	34,6lm/W
Färgtemperatur	4000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>50 000h
Effektfaktor	PF>0,90
Ta nominel:	+25°C
Inrush current	0,98A / 38µs
Antal armaturer på automatsäkring	<b>B 10A:</b> 126, <b>B 16A:</b> 200, <b>C 10A:</b> 208, <b>C 16A:</b> 340

## Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer, BIM Revit

