



Allmän information

Typ armatur	Stolpe
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	PMMA, opal
Typ ljuskälla	LED modul + driver
Ljusstyrning	Ej dimbar
Netto / Bruttovikt armatur	4,92kg / 6,54kg
Förpackning mått [cm]	22x54,5x54,5
LED	Cree JK3030 DK190804VA03 (Produktblad)
Drivdon	Philips Xi BP 40W 0.3-1.0A S 230V C123_sXt (Produktblad)
Drivdon hållbarhet	100000h
Led modul effekt	27,2W
Armatur effekt	32W
Lumen modul	4380lm
Lumen ut	3069lm
Led modul effekt	161lm/W
Armaturens effekt	95,9lm/W
ULOR	0%
Färgtemperatur	4000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>72 000h
LED-fotobiologiskt hot	RG0 or RG1
Effektfaktor	PF 0,98
THD-faktor	9%
Spänning	6 / 10kV
Ta nominel:	+25°C
Maximal omgivningstemperatur	-30 ...+25°C
Inrush current	19A / 210µs

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer, BIM Revit, BIM ArchiCAD