


Art	E-nr	Färg	RAL
718AL	7701409	ALUMINIUM	9006
718GR	7701411	GRAFIT	7016
718W	7701410	VIT	9003

## Allmän information

Typ armatur	Vägg/takarmatur
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Opal polykarbonat, UV stabiliserat
Typ ljuskälla	LED modul AC
Ljusstyrning	Dimbar (Triac)
Netto / Bruttovikt armatur	2,25kg / 2,55kg
Förpackning mått [cm]	30,5x30,5x11
LED	Lumens DLM 100C 10W 830 230V F201 V0,5 3K (☞ Produktblad)
Led modul effekt	10W
Armatur effekt	10W
Lumen modul	911lm
Lumen ut	574lm
Led modul effekt	91,1lm/W
Armaturens effekt	57,4lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	50 000h
Energieffektivitetsindex (EEI)	 / ☞ EPREL
Effektfaktor	PF 0,95
THD-faktor	25%
Ta nominel:	+25°C
Inrush current	50mA / 60ms

## Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer, BIM Revit, BIM ArchiCAD

