


Art.nr	El.nummer	Farge	RAL
1280AL	3110096	ALUMINIUM	9006
1280GR	3110097	GRAFITT	7016

Generell informasjon

Type armatur	Pullert
Materiale	Pulver lakkert aluminiumstøp
Avdeknings materiale/optikk	PMMA, klar
Type lyskilde	LED modul + driver
Lysstyring	Ikke dimbar
Netto / Brutto vekt armatur	11,63kg / 13,46kg
Forpakkingsstørrelse [cm]	23x22x113
5xLED moduler	Cree DK180501 V3 JK3030 3V 3K (⊗ Produktblad/FDV)
Driver	Philips Xitanium 20W/m 0.15-0,5A 54V 230V (⊗ Produktblad/FDV)
Effekt W	17,9W
Armatureffekt	22W
Modul lumen	2434lm
Lumen ut	1586lm
Modul effektivitet	136lm/W
Armatur Lumen/Watt	72,1lm/W
ULOR	10%
Fargetemperatur	3000K
Farvekonsistens (McAdam-Ellipse)	SDCM3
Fargegjengivelsesindeks	80
Beregnet levetid L70/B50 ved 25°C	>50 000h
LED fotobiologisk trussel	RG0 or RG1
Energieffektivitetsindeks (EEI)	 / EPREL
Virkningsgrad	PF>0,98
Ta nominel:	+25°C
Inrush current	18A/250µs
Antall armaturer på automatsikring	B 10A: 21, B 16A: 34, C 10A: 35, C 16A: 57

Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual, BIM Revit, BIM ArchiCAD