



## Generell informasjon

Type armatur	Stolpe
Materiale	Pulver lakkert aluminiumstøp
Avdeknings materiale/optikk	PMMA, klar
Type lyskilde	LED modul + driver
Lysstyring	Dimbar (Triac)
Forpakkingsstørrelse [cm]	15x15x260
LED	Cree DK210704 V2 JB2835 3V 3K (⚡ Produktblad/FDV)
Driver	TCI MICRO MD 10W 350mA 127040 Triac (⚡ Produktblad/FDV)
Effekt W	7,4W
Armatureffekt	9,1W
Modul lumen	1370lm
Lumen ut	907lm
Modul effektivitet	185,1lm/W
Armatur Lumen/Watt	99,7lm/W
ULOR	1%
Fargetemperatur	3000K
Farvekonsistens (McAdam-Ellipse)	SDCM3
Fargegjengivelsesindeks	80
Beregnet levetid L70/B50 ved 25°C	>72 000h
Energieffektivitetsindeks (EEI)	 / ⚡ EPREL
Virkningsgrad	PF 0,9
THD-faktor	10%
Ta nominel:	+25°C
Maksimal omgivelsestemperatur	+40°C
Inrush current	2A / 50µs



## Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual

