



| Art.nr | El.nummer | Farge | RAL |
|--------|-----------|-----------|------|
| 1742AL | 3102465 | ALUMINIUM | 9006 |
| 1742GR | 3102466 | GRAFITT | 7016 |
| 1742W | 3102467 | HVIT | 9003 |
| 1742B | 3104135 | SORT | 9005 |

Generell informasjon

| | |
|-----------------------------------|---|
| Type armatur | Veggarmatur |
| Materiale | Pulver lakkert aluminiumstøp |
| Avdeknings materiale/optikk | Glass - herdet, klar |
| Type lyskilde | LED modul AC |
| Lysstyring | Dimbar (Triac) |
| Netto / Brutto vekt armatur | 1,1kg / 1,16kg |
| LED | Lumens EDC 38C 8W xxx 230V A101 3K (⊗ Produktblad/FDV) |
| Effekt W | 8W |
| Armatureffekt | 8W |
| Modul lumen | 756lm |
| Lumen ut | 563lm |
| Modul effektivitet | 94,5lm/W |
| Armatur Lumen/Watt | 70,4lm/W |
| ULOR | 0% |
| Fargetemperatur | 3000K |
| Farvekonsistens (McAdam-Ellipse) | SDCM3 |
| Fargegjengivelsesindeks | 80 |
| Beregnet levetid L70/B50 ved 25°C | >50 000h |
| LED fotobiologisk trussel | RG0 or RG1 |
| Energieffektivitetsindeks (EEI) |  /  EPREL |
| Virkningsgrad | PF>0,98 |
| THD-faktor | < 20% |
| Ta nominel: | +25°C |
| Maksimal omgivelsestemperatur | -35...+25°C |
| Inrush current | 35mA / 60ms |

Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual