



Art.nr	El.nummer	Farge	RAL
657GA	3101957	GALVANISERT STÅL	-
657B	3101958	SORT	9005

Generell informasjon

Type armatur	Veggarmatur
Materiale	Front - Rustfritt stål, galvanisert stål, lakkert stål
Avdeknings materiale/optikk	Glass - herdet, frostet
Andre materialer	Bakplate - Aluminium
Type lyskilde	LED modul AC
Lysstyring	Dimbar (Triac)
Netto / Brutto vekt armatur	2,85kg / 3,6kg
Forpakkingsstørrelse [cm]	27,5x22,8x33,5
LED	Lumens LNM/140X30/4R5W/830/230V/C
Effekt W	4,5W
Armatureffekt	4,5W
Modul lumen	428lm
Lumen ut	262lm
Modul effektivitet	95,1lm/W
Armatur Lumen/Watt	58,2lm/W
Fargetemperatur	3000K
Farvekonsistens (McAdam-Ellipse)	SDCM3
Fargegjengivelsesindeks	80
Beregnet levetid L70/B50 ved 25°C	50 000h
Virkningsgrad	PF > 0,99
Ta nominal:	+25°C
Maksimal omgivelsestemperatur	+35°C
Inrush current	27,2mA/500µs
Antall armaturer på automatsikring	B 10A: 95, B 16A: 151, C 10A: 157, C 16A: 256

Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual