



| Art.nr | El.nummer | Farge     | RAL  |
|--------|-----------|-----------|------|
| 557AL  | 3185557   | ALUMINIUM | 9006 |
| 557GR  | 3185558   | GRAFITT   | 7016 |

## Generell informasjon

|                                   |   |
|-----------------------------------|---|
| Type armatur                      | Pullert   |
| Materiale                         | Pulver lakkert aluminiumstøp  |
| Avdeknings materiale/optikk       | Klar polykarbonat, UV stabilisert   |
| Type lyskilde                     | LED modul + driver  |
| Lysstyring                        | Ikke dimbar   |
| Netto / Brutto vekt armatur       | 10,84kg / 13,16kg   |
| Forpakkingsstørrelse [cm]         | 31,5x29x99  |
| LED                               | Philips Fortimo SLM C 1208 L15 2024 G7 3K (⊗ Produktblad/FDV)                                 |
| Driver                            | Philips Xitanium 36W/m 929001486006 (⊗ Produktblad/FDV)                                       |
| Effekt W                          | 19W   |
| Armatureffekt                     | 21,8W   |
| Modul lumen                       | 3137lm  |
| Lumen ut                          | 556lm   |
| Modul effektivitet                | 165,1lm/W   |
| Armatur Lumen/Watt                | 25,5lm/W  |
| ULOR                              | 0%  |
| Fargetemperatur                   | 3000K   |
| Farvekonsistens (McAdam-Ellipse)  | SDCM3   |
| Fargegjengivelsesindeks           | 80  |
| Beregnet levetid L70/B50 ved 25°C | >50 000h  |
| Energieffektivitetsindeks (EEI)   |  / ⊗ EPREL |
| THD-faktor                        | 20%   |
| Ta nominal:                       | +25°C   |
| Inrush current                    | 4,6A / 65μs   |

## Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual