



Art.nr	El.nummer	Farge	RAL
1561GA	3102476	GALVANISERT STÅL	-
1561B	3102477	SORT	9005

Generell informasjon

Type armatur	Pullert
Materiale	Galvanisert stål Galvanisert stål og lakker stål
Type lyskilde	LED modul AC
Lysstyring	Dimbar (Triac)
Netto / Brutto vekt armatur	6,06kg / 6,68kg
Forpakkingsstørrelse [cm]	89,5x11,5x11,5
LED	Lumens EDC 38C 4W xxx 230V A101 3K (⊗ Produktblad/FDV)
Effekt W	4W
Armatureffekt	4W
Modul lumen	439lm
Lumen ut	330lm
Modul effektivitet	109,8lm/W
Armatur Lumen/Watt	82,5lm/W
Fargetemperatur	3000K
Farvekonsistens (McAdam-Ellipse)	SDCM3
Fargegjengivelsesindeks	80
Beregnet levetid L70/B50 ved 25°C	>50 000h
LED fotobiologisk trussel	RG0 or RG1
Energieffektivitetsindeks (EEL)	 /  EPREL
Virkningsgrad	PF>0,98
THD-faktor	< 20%
Ta nominel:	+25°C
Maksimal omgivelsestemperatur	-35...+25°C
Inrush current	17mA / 60ms

Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual

